


F30α Sensor

General Purpose Sensor




DESCRIPTION AND FEATURES

The F-series sensors are designed to incorporate the latest advances in materials and transducer design principles. These sensors unlike the resonant sensors (R-series) have a very high sensitivity and flat response in the bandwidth of operation. The F30A is a wideband sensor with a flat frequency response over the range of 150 – 750 kHz. This sensor is an ideal candidate for applications requiring high bandwidth for frequency analysis of the AE signals for noise discrimination and source identification. This sensor features a rugged steel construction and an SMA connector exiting from the side of the sensor.

APPLICATIONS

This sensor is well suited for structural health monitoring of large structures like storage tanks, pipelines etc. Flat response of these sensors help eliminate the sharp rise and fall in the sensitivity with frequency commonly seen in resonant sensors, providing additional information for engineers to analyze. Wideband sensors are well suited for research applications where a high fidelity AE response is required. It can be easily mounted using epoxy.



OPERATING SPECIFICATIONS

Dynamic

Peak Sensitivity, Ref 1V/(m/s).....	58 dB
Peak Sensitivity, Ref 1V/μbar.....	-63 dB
Operating Frequency Range	150-750 kHz
Resonant Frequency, Ref 1V/(m/s)	300 kHz
Resonant Frequency, Ref 1V/μbar	300 kHz
Directionality.....	+/-1.5 dB

Environmental

Temperature Range	-45 to 145°C
Shock Limit.....	500 g

Physical

Dimensions	0.75"OD X 0.880"H
.....	19.0 mm OD X 22.4 mm H
Weight	34 grams
Case Material	Stainless steel
Face Material.....	Ceramic
Connector	SMA
Connector Locations	Side
Sensor to Preamp Cable (1 or 2 meters)	
.....	1232-X-SMA

Electrical

Shielding for EMI	Fully shielded
-------------------------	----------------

ORDERING INFORMATION AND ACCESSORIES

F30α	F30α or F30a
Cable (specify length in 'm')	1232-X-SMA
Magnetic Hold-Down	MHR15A
Pre-amplifier	IL-LP-30S, PreampOne

Sensors include

Characterization Certificate & Warranty

