


Nano30 Sensor

Medium Frequency Resonant Miniature Sensor



DESCRIPTION AND FEATURES

The Nano-30 miniature AE sensor has a resonant response at 300KHz and a good frequency response over the range of 125 – 750 kHz. Its size makes the sensor an ideal candidate for applications where small size is important. The sensor features a small, 1 meter, integral coax cable, which exits from the side of the sensor with a BNC connector on the end.

APPLICATIONS

The sensor can be used in any application requiring a small, mid-band frequency response. It can easily be mounted using epoxy and can be mounted in small and tight spaces.

OPERATING SPECIFICATIONS

Dynamic

Peak Sensitivity, Ref V/(m/s)	62 dB
Peak Sensitivity, Ref V/ μ bar	-72 dB
Operating Frequency Range	125-750 KHz
Resonant Frequency, Ref V/(m/s)	140 KHz
Resonant Frequency, Ref V/ μ bar	300 KHz
Directionality	+/- 1.5 dB

Environmental

Temperature Range	-65 to 177°C
Shock Limit	500 g
Completely enclosed crystal for RFI/EMI immunity	

Physical

Dimensions	0.3"OD X 0.3"H
	8 mm OD X 8 mm H
Weight	2 grams (8 with cable & connector)
Case Material	Stainless steel
Face Material	Ceramic
Connector	BNC
Connector Locations	Side

ORDERING INFORMATION AND ACCESSORIES

Nano30	Nano30
Cable (specify cable length in meters)	1 m
Preamplifier	0/2/4, 2/4/6
Amplifier Subsystems	AE2A, AE5A
Preamp to System Cable (specify length in 'm')	1234-X

Sensors include

NIST Calibration Certificate & Warranty

